

IAQ meter

Desktop Carbon Dioxide monitor 7788/7787



7788



7787

- ▲ DIGITAL DESKTOP TYPE GIVES YOU A GREEN DAY!
- ▲ 15 DEGREE TILT ANGLE FOR EASY TO SEE AND READ
- ▲ REAL TIME CLOCK AND CALENDAR ARE DISPLAYED
- ▲ WARNING CARBON DIOXIDE LEVEL FROM 1000-5000PPM
- ▲ SUPER LARGE LCD DISPLAY CO2 VALUE (WITH GOOD, NORMAL, POOR AIR QUALITY INDICATOR), YEAR-MONTH-DATE , HOUR-MINUTE , AIR TEMP. & RELATIVE HUMIDITY
- ▲ MAX. /MIN. RECALL FUNCTION
- ▲ TEMPERATURE UNIT IS SWITCHABLE
- ▲ REAL TIME CLOCK IS ADJUSTABLE
- ▲ NDIR (NON-DISPERSIVE INFRARED) WAVEGUIDE TECH.
- ▲ W/ ABC (AUTOMATIC BACKGROUND CALIBRATION)
- ▲ LONG TIME DRIFT COMPENSATION
- ▲ BRIGHT LED VISIBLE INDICATES POWER IS ON
- ▲ AUDIBLE ALARM WARNS CO2 AIR QUALITY IS POOR
- ▲ MONITORING RESIDENTIAL , COMMERCIAL AND HOME AIR QUALITY
- ▲ CO2 ALARM OUTPUT DESIGN DRIVES RELAY TO CONTROL VENTILATION SYSTEM, SUCH AS FAN OR AIR CONDITIONER (7788 ONLY)

	7788	7787
Measuring range		
CO2	0~9999 ppm, (2001~9999 ppm out of scale range)	
Temperature	-10~60°C (14~140°F)	
Relative Humidity	0.1%~99.9%RH	
Resolution	1ppm , 0.1°C/°F, 0.1%RH	
Accuracy		
CO2	±50ppm±5% of reading(0~2000ppm) Others range accuracy are not specified	
Temperature	±0.6°C/±0.9°F	
Relative Humidity	±3%RH (at 25°C, 10~90%RH) ±5%RH (at 25°C , others)	±5%RH (at 25°C, 10~90%RH) ±7%RH (at 25°C , others)
Warm-up time	30 seconds	
Response time		
CO2	<2 minutes (90% step change)	
Tair	<2 mins (90% step change)	
RH	<10 minutes (90% step change)	
RELAY (1A 30VDC/0.5A 125VAC)	YES	NO
LCD size (mm, HxW)	60x82	
Operating condition	0~50°C , 5~80% RH (avoid condensation)	
Storage condition	-20~ 50°C, 5~90%RH(avoid condensation)	
Power supply	5VDC adaptor (±10%), ≥500mA	
Meter size	120 x 80 mm (Diameter x Depth)	
Weight	200g	
Standard package	Meter, manual , adaptor 100-240VAC , plain box	



**EASTERN
ENERGY**

www.eastern-energy.net

email: info@ete.co.th