

HI 151-00 Folding Pocket Thermometer

- $\pm 0.3^{\circ}\text{C}$ accuracy
- CAL CHECK[®]
- Stainless steel folding probe with penetration tip
- Enables angled measurement
- Ergonomic
- Auto shut-off

The folding Checktemp[®]4 provides practical temperature measurement for the food service industry.

Special attention was given to the ergonomic form of Checktemp[®]4. This thermometer fits comfortably and securely in your hand. The LCD on the side of the handle is easy to see and read. The fast responding, fold-away probe is made of high quality, stainless steel and can penetrate semi-frozen and semi-solid foods like meats, ice cream and cheeses. When you are finished using your Checktemp[®]4, wipe the probe clean and fold it away. Checktemp[®]4 automatically turns OFF so you can safely carry it in your pocket.

CAL CHECK[®]

As you unfold the stainless steel probe, the Checktemp[®] 4 automatically turns ON and immediately performs a calibration test. This unique HANNA feature, CAL CHECK[®], provides the security of knowing you have accurate measurements. CAL CHECK[®] also lets you know if your battery level is low or if your meter requires recalibration.

ORDERING INFORMATION

HI 151-00 (Checktemp[®]4 C) is supplied complete with battery and instructions

HI 151-01 (Checktemp[®]4 F) is supplied complete with battery and instructions

HI 151-001 (Checktemp[®]4 C) is supplied complete with calibration certificate, battery and instructions

HI 151-011 (Checktemp[®]4 F) is supplied complete with calibration certificate, battery and instructions

HI 151-02 (Checktemp[®]4 C) $\pm 0.5^{\circ}\text{C}$ accuracy, without CAL CHECK is supplied complete with battery and instructions



Turns on and off by opening and closing the probe

SPECIFICATIONS	HI 151-00 (Checktemp [®] 4C)
Range	-50.0 to 220°C
Resolution	0.1°C (-50.0 to 199.9°C); 1°C (200 to 220°C)
Accuracy	$\pm 0.3^{\circ}\text{C} \pm 1$ digit (-20.0 to 90.0°C); $\pm 1\%$ F.S. ± 1 digit (outside)
Calibration Check	automatic, at start-up
Probe	stainless steel probe with penetration tip; 117 x dia 3.5 mm (4.6 x dia 0.14")
Battery Type / Life	1.5V AA / approximately 25,000 hours of continuous use; auto-off after 8 minutes of non-use
Environment	0 to 50°C (32 to 122°F); RH max 95%
Dimensions	165 x 50 x 20 mm (6.5 x 2.0 x 0.8")
Weight	100 g (3.5 oz.)



**EASTERN
ENERGY**

With Great Products, Come Great Results™

www.eastern-energy.net

Email: info@ete.co.th