

6 meters in one

Combines an anemometer, hygrometer, thermometer, sound and light meter into a single hand-held unit. Also reads any type-K thermocouple probe. Results are displayed on a large dual LCD with low battery and out-of-range indications. Features touch-tone buttons, min/max, auto power off and hold functions. Comes ready to use in a soft carrying case with RS232 computer port, instructions, 6 AAA batteries, easel back, and a tripod screw. N.I.S.T. Traceable Certificate of Calibration available.

DIM: 9¾" × 2¾" × 1¼" (248 × 70 × 32 mm). WEIGHT: 12 oz (340 g).

No.	Description
850069	Environmental Quality w/ Sound
850069C	Environmental Quality w/ Sound Certified
800060-77	Type-K Thermocouple Probes
840057	RS232 Computer Cable
840058	USB Power Cable
840094	RS232 to USB Adaptor Cable
840097	AC Adaptor
850016	2-Point Acoustical Calibrator
850080	Software
840091	Sound Meter Windscreen
840093	Field Tripod



	Range	Resolution	Accuracy
°C ambient	0 to 50	0.1	±1.2°C
°F ambient	32 to 122		±2.5°F
°C Type K	-100 to 1300		±(1% + 1°C)
°F Type K	-148 to 2372		±(1% + 2°F)
RH	10 to 95%	0.1	<70% RH ±4% >70% RH ±(4% rdg + 1.2% RH)
Airspeed m/s	0.4 to 30.0		<20 m/s ±3% fs >20 m/s ±4% fs
Airspeed km/h	1.4 to 108.0		
Airspeed mile/h	0.9 to 67.0		
Airspeed knots	0.8 to 58.3		
Airspeed ft/min	80 to 5910	1	
Lux	0 to 2,000 1800 to 20,000	1 10	±5% rdg + 8 d
Foot Candle	0 to 204.0 170 to 1860	0.1 1	
dB	35 to 130	0.1	23+5°C ±1.5 dB

