

Mini Environment Meters



EMC
EN: 61326

DT-82 Mini Anemometer

Specification

Function	Range	Accuracy
m/s(meter per second)	0.40~25.00	±3.5% ±0.20m/s
ft/min(feet per minute)	80~2980	±3.5% ±40ft/min
km/h(kilometers per hour)	1.4~54.0	±3.5% ±0.8km/h
MPH(miles per hour)	0.9~33.0	±3.5% ±0.4MPH
Knots(nautical miles per hour)	0.8~29.0	±3.5% ±0.4knots

Size(HxWxD): 165mm x 54mm x 34mm

Weight: 139g

Accessories :

9V battery, Clamshell.



Model: DT-82



DT-85A Mini Sound Level Meter

85A/85C Mini Sound level meter have a wide dynamic range from 35 to 130dB. They have different frequency weighting A and C to respond to human sense or machine monitoring purposes. For different sound pattern, they also supply Fast and Slow time constant setting.

Specification

Function	Range	Accuracy	85A
Sound Level	35 ~ 130dB	±3.0dB(ref 94dB@1kHz)	*
Frequency	31.5 ~8kHz		*
Frequency Weighting			A

Size(HxWxD): 128mm x 54mm x 34mm

Weight: 131g

Accessories :

9V battery, Clamshell.



Model: DT-85A



DT-86 Mini Light Meter

Specification

Function	Range	Resolution	Accuracy
Light	40,000Lux /Fc	0.1Lux/0.01Fc	±5%±10d(<10,000Lux)
Measuring Rate	1.5 times/second		

Size(HxWxD): 157mm x 54mm x 34mm

Weight: 138g

Accessories :

9V battery, Clamshell.



Model: DT-86