USB Datalogger w/PDF report

NEW



Temp. +%RH logger w/PDF (Interface: USB)

- A Plug & Play temp. & %RH logger with USB 2.0 connector
- **▲** Software & driver are not required for any operation
- A Automatically generate a PDF and Excel report while plugged into computer
- **A** High accuracy thermistor and capacitive RH sensor
- **⚠** Completely programmable by users for maximum flexibility includes: 6 languages, sampling interval, start delay, alarm delay, unit, alarm range, alarm type, password and user name
- **⚠** Compact, light and IP65 (not include sensor area)
- **▲** Big LCD provides excellent viewing experience
- **⚠** Count key to review max. & min value of logged data
- **▲** Dual color LED provides instant status indicator: REC and High/Low temperature
- **▲ Large memory capacity, 24000 Temp. &24000 %rH points.**
- ♠ Powered by 2pcs CR2032 batteries. Easy replacement.
- Mark key to provide 8 marking during transition period
- **⚠** One key operation to know leftover battery life time
- ♠ PDF file contains summary, graph and detailed data list

▲EN12830 and RoHS compliance



ACCUPATION OF THE PARTY OF THE		eport.			
M	N				
No bothering	Company Name		ie Function ta logger	8N (#	
computer setting!!	Production data Production of Program and an Original Streets The challed	7. Apr. 500 (4.00) (4.0	Total Constitution (Constitution Constitution Cons		
Driver, Software and reader are all not required!!	Parameter (Appl. Assets) Page Assets (Appl. Asse	Management to the Park of the	Parameter (App. Assets) In the State (App. Assets) Residence (App. Assets) Res	tecentrals that being	
		tengeratura	-		

Plug into PC to generate PDF

Model 88162

Temp. range	NTC thermistor, -30~70°C, -22~158°F		
Temp. resolution	0.1°C , 0.1°F		
Temp. Accuracy	+/-0.5°C		
Humidity range	Capacitor, 0.1~99.9%rH		
Humidity resolution	0.1%rH		
Humidity Accuracy	+/-3% (at 25°C, 10~90%), others +/-5%		
Sampling points	24000 Temp. and 24000 Humidity		
Meter size	110(L)*45(W)*17(T) mm		
Operating temp.	-30~70°C (Logging status); room temp.(PC mode)		
Operating RH%	Humidity < 90%		
Storage temp.	-40~85°C		
Storage RH%	Humidity < 90%		
Weight	~80g		
Battery	2PC 3.0V CR2032 , 3 months life time		
Sampling interval	30 seconds, 5,10,30,60,90,120 minutes		
Start delay	0, 5,30,45,60, 90,120 minutes and 24 hours		
Alarm range	Programmable from -30 to 70°C and 1~99%RH		
Alarm delay	0, 5,30,45,60, 90,120 minutes		
Alarm type	Single Event, Cumulative, Disable		
Operation keys	3 Keys (Start/Stop key & Mark key & Count key)		
LED indicator	REC, High / Low alarm		
Standard package	Logger, manual, paper box		

Eastern Energy Co., Ltd. 40/4 Vitoondumri Rd., Banbueng Banbueng, Chonburi, Thailand

