

A single dynamic 30 to 130 dB range

Eliminates the need to manually select ranges and prevents data errors during range changes in auto-ranging models. All test parameters are simultaneously displayed on a large, bright backlit display, featuring 0.1 dB resolution and a bar graph. Automatically log up to 31,000 records for later download, or manually save and recall 99 data points with date and time stamp directly on the meter's LCD. The bidirectional USB port and software also enable control of the meter via its on-screen image. Accurate within ± 1.4 dB, and meets or exceeds all other specs for an IEC 61672:2013 Class 2 and ANSI S1.4:2014 Type 2 meters. Also features A/C and fast/slow weighting scales, min/max, over/under alarms, AC or DC recorder output and auto power off. Calibrate in compliance with OSHA using Acoustical Calibrator 850016. Comes in a foam-lined protective carrying case, complete with a windscreen, USB computer connection cable, software, instructions, calibration tool, recorder output plug, and 4 AA batteries, which provide about 30 hours of use. The optional microphone extension cable enables remote measurements. N.I.S.T. Traceable Certificate of Calibration available (MODEL 850013C).

DIM: $10\frac{3}{4}" \times 3\frac{1}{2}" \times 1\frac{1}{2}"$ (273 x 89 x 38 MM). WEIGHT: 14.6 oz (414 g).

No.	Description
850013	Adv. Datalogging Sound Meter
850013C	Adv. Datalogging Sound Meter Certified
800003	AC Adaptor
840095	16' Microphone Extension Cable
850016	2-Pt. Acoustical Calibrator
840091	Windscreen Replacement
840093	Field Tripod

Range	Resolution	Accuracy
32 to 130 dB	0.1 dB	± 1.4 dB



Contact :

EASTERN ENERGY CO.,LTD. (HEAD OFFICE)

40/4 Vitoondumri Rd., Banbueng, Banbueng, Chonburi 20170

Tel: 0-3844-6117 Fax: 0-3844-6200

Email: info@ete.co.th

