

TM-802 Formaldehyde Meter

NEW

- Can be displayed simultaneously formaldehyde, temperature, humidity, easy to monitor
- Occupational safety monitoring shows TWA (8 hours) and STEL (15 mins)
- Use high-precision electrochemical sensor
- The maximum / minimum / average hold
- Stores 200 records manually
- Formaldehyde maximum and minimum alarm value setting
- Data hold
- Back light display



HCHO measurement

Range	0.00~5.00 ppm (mg / m ³)
Resolution	0.01ppm (mg / m ³)
Accuracy	±5% of reading ±0.03 PPM
Response time	30 seconds

Temperature measurement

Range	-20~50°C / -4~122°F
Resolution	0.1°C / 0.1°F
Accuracy	1.0°C / 1.8°F

Humidity measurement

Range	5%~95% RH
Resolution	0.1RH
Accuracy	±5.0%RH (20~80%); ±8.0%RH (<20%, >80%)

Dimension	191 x 73 x 35mm (L x W x H)
Weight	250g (excluding the batteries)
Power	LR03 (AAA)1.5V x6 batteries DC adaptor 9V/0.5A (9mm) (optional)



Contact :

EASTERN ENERGY CO.,LTD. (HEAD OFFICE)

40/4 Vitoondumri Rd., Banbueng, Banbueng, Chonburi 20170

Tel: 0-3844-6117 Fax: 0-3844-6200

Email: info@ete.co.th