



EMC
EN: 61326

- Memory for 10 complete data sets
- LED light & audible alarm

- High Quality Sensor



Model CO-110



CO-110 Carbon Monoxide Meter detects the presence of carbon monoxide (CO) and measures concentrations between 1-1000 parts per million (PPM). The Meter indicates the presence of CO by a reading on the LCD and a beeper tone. The beeper function much like clicking of a Geiger counter: Above 200 PPM, the beeper sounds continuously with the concentration of CO. From 35 PPM to 200 PPM, the beeper sounds discontinuously with the concentration of CO.

Features

Digital LCD Display
Auto/manual zero
Memory for 10 complete data sets
Record mode
Red & Blue LED light and audible alarm
High Accuracy, quick response
Pocket size and easy to use
Fast sampling
Max Hold
Data Hold
Above 200 PPM, the beeper sounds continuously

Specifications

Operating temperature	0°C to 50.0°C
Storage temperature	-30°C to 60.0°C
Operating humidity	0-90% relative humidity (non-condensing)
Measurement Range	0 to 1000PPM
Measurement Resolution	1PPM
Accuracy	±5% or ±10PPM
Warm up period	Less than 2 seconds
Battery	9V, NEDA 1604A or equivalent
Sensor type	Stabilized electrochemical Gas-specific (CO)
Typical sensor life	3 years

Size(HxWxD) 2mm x 52mm x 29mm
Weight 84g

Accessories :

3.6V battery and Gift box with carrying case.



Contact :

EASTERN ENERGY CO.,LTD. (HEAD OFFICE)

40/4 Vitoondumri Rd., Banbueng, Banbueng, Chonburi 20170

Tel: 0-3844-6117 Fax: 0-3844-6200

Email: info@ete.co.th