



## 4 Channel K Thermocouple SD Card Logger 88598

- Super big LCD portable / wallmount SD card logger
- Measure and Log 4 temperature at once by using quick response thermocouple probes
- Programmable independent high/low alarm of each channel
- One button press operation to display T1-T2
- Display temperature change from baseline
- Temperature offset function for adjustment purpose



Model	88598
K temp. range	-200~1370°C , -328~2498°F
K temp. resolution	0.1°C , 0.1°F
K temp. accuracy (under 18~28°C ambient temp.)	±(0.3% rdg +1°C)
Sampling rate	Programmable from 1 second up
LCD size (mm, HxW)	47x104
Operating temp.	0~50°C
Operating RH%	Humidity < 80%
Storage temp.	-20~50°C
Storage RH%	Humidity < 90%
Dimension(mm,LxWxT)	152x100x39
Weight	~300g
Battery	4pcs AA alkaline batteries or 9V adaptor
Standard Package	Meter, 2pcs bead type K thermocouple, battery, manual, SD card, plain box
Optional Accessory	K type thermocouple (custom made thermocouple is available upon request)

**Wallmount with big display!!**


**No bothering computer setting!!**

**Log anytime anywhere!!**

**Leave your PC at home !!**



**Ordering Code**  
**VZ88598AZ, 88598 logger**  
**VB1099EX, 9V universal adaptor**  
**VE60A000, 1M long K bead cable**  
**VE60A0YK, 4M long K bead cable**



**K BEAD TYPE THERMOCOUPLE**  
 P/N:VE60A000  
 Temp. Range:-50~200°C  
 Length: 1M long  
 P/N:VE60A0YK  
 Temp. Range:-50~200°C  
 Length: 4M long  
 Other custom made probe: immersion, penetrate, Surface.....etc are available Upon request



**9V UNIVERSAL ADAPTOR**  
 P/N:VB1099EX  
 Input:100~240 VDC  
 Output:9VDC, 0.9A  
 3 plugs included:US/UK/EU

**Contact :**

**EASTERN ENERGY CO.,LTD. (HEAD OFFICE)**  
 40/4 Vitoondumri Rd., Banbueng, Banbueng,  
 Chonburi 20170  
 Tel: 0-3844-6117 Fax: 0-3844-6200  
 Email: info@ete.co.th

