


## TIME® 7120/7122/7126

### VIBRATION PEN

#### Standard Delivery

- Main unit 1
- Battery 2
- Protection pocket 1
- TIME certificate 1
- Warranty card 1
- Instruction manual 1



#### Features

- Used for fast failure detecting of motor, electric fan, pump, air compressor, machine tools and so on
- Compact size, small weight, easy handling
- Prompt testing of vibration on the workshop machines
- For quick checking of unbalance misalignment, bearings and gears
- Guard against mechanical malfunction
- Holding tested value for 40 seconds
- TIME®7120 is used specially for velocity testing
- TIME®7122 is used specially for displacement testing
- TIME®7126 is used for testing of acceleration, velocity and displacement



#### Technical Specification

	TV200	TV220	TV260
Model	TIME®7120	TIME®7122	TIME®7126
Parameters	RMS of vibration velocity (mm/s)	Displacement	Acceleration, Velocity, Displacement
Testing range	Velocity: 0.1mm/s~199.9mm/s	Displacement: 0.01mm~1.999mm (peak~peak)	Acceleration:0.1-199.9m/s <sup>2</sup> (peak) Velocity: 0.1-199.9 mm/s (RMS) Displacement: 0.01-1.999 mm (peak-peak)
Frequency range	Velocity: 10Hz-1KHz, Acceleration: 10Hz-1KHz	Displacement: 10Hz~500Hz	Velocity: 10Hz~1KHz Displacement: 10Hz~500Hz Acceleration:10Hz~1KHz
Tolerance	±5%±2		
Display	3½digits LCD		
Power	Two button batteries(LR44 or SR44)		
Battery capacity	Approx. 4.5 hours working continuously		
Operating temperature	0°C~40°C		
Humidity	<85%		
Dimensions (mm)	150×22×18		
Weight (g)	55(including batteries)		