

GD-3303

Gas Leakage Detector



GD-3303

REFRIGERANT GAS LEAKAGE DETECTOR

INTRODUCTION

The Refrigerant Leak Detector detects all CFC refrigerants such as R-22, R-124, R-11 and R-12. The ultra-sensitive long life sensor detects the more current, difficult-to-detect HFC refrigerants such as R-134a, R-404A, and new R-22 replacements, R-410A and R-407C. The Refrigerant Leak Detector's long, slim gooseneck probe design is easy to use in close areas and for extending into hard-to-reach areas. It's adjustable alarm, easy one-hand operation and impact resistance storage case add up to value and convenience.

SPECIFICATIONS

- Sensitivity : 100ppm of R- 134a/ R- 22
Sensor Type : Low Power Semiconductor
Warm Up Time : Approx.1 minute
Response Time : Less than 2 seconds (up to 40% LEL)
Alarm : Visible & Audible at 10% LEL for all chlorofluorocarbons (CFC).
Power Supply : 3"C" cell batteries
Battery Life : 8 hours continuous use, typical
Duty Cycle : Continuous
Probe Length: : 16"Ncentrations or Gases.
Dimensions : 221x72x46mm
Weight : 498g



Table with 2 columns: R-12 ALTERNATIVES and R-22 ALTERNATIVES. Lists various refrigerant models and their alternatives.

ACCESSORIES

Carrying Case, Instruction Manual, Battery.



EASTERN ENERGY CO.,LTD. (HEAD OFFICE)

40/4 Vitoondumri Rd., Banbueng, Banbueng, Chonburi 20170
Tel: 0-3844-6117, Fax: 0-3844-6200 Email: info@ete.co.th