


**Radalert 100X™ Nuclear Radiation Monitor**

The Radalert 100X™ measures alpha, beta, gamma, and X-radiation. Its digital display shows readings in your choice of counts per minute (CPM) $\mu\text{Sv/hr}$ or mR/hr or in accumulated counts. A red LED blinks and a beeper chirps with each count (the chirp can be muted). An audible alert sounds when the radiation reaches a user-adjustable level.

- Monitor personal radiation exposure
- Monitor an area or perimeter
- Detect radiation leaks and contamination
- Ensure regulatory compliance
- Monitor changes in background radiation
- Demonstrate principles of nuclear physics
- Check for radioactive minerals in the earth

Technical Specifications

Detector:	Halogen-quenched Geiger-Mueller tube (LND 712) Mica end window density 1.5-2.0 mg/cm ² Side wall is 0.012" #446 stainless steel Detects Alpha, Beta, Gamma, and X-radiation
Display:	4-digit liquid crystal display with mode indicators
Operating Range:	$\mu\text{Sv/hr}$: .000-1,100 mR/hr : .000-110 CPM: 0 to 350,000 CPS: 0 to 3,500 Total: 0 to 9,999,000 counts
Calibration:	Cesium -137 (gamma)
Gamma Sensitivity:	1,200 CPM/mR/hr referenced to Cs-137
Accuracy:	$\pm 10\%$ typical; $\pm 15\%$ maximum
Alert Range:	User-adjustable alert level to 500 $\mu\text{Sv/hr}$ & 60,000 CPM
Count Light:	Red LED flashes with each count
Audio:	Beeper chirps for each count (can be muted)
Ports:	• Output: Stereo 3.5 mm jack sends counts to computers, data loggers, other CMOS-compatible devices, earphones, and educational data collection systems. 0-9 V, 1 kOhm impedance. • Input: 2.5 mm mono jack provides calibration input. 0-3.3 V, > 5 μs width, rising edge triggered.
Anti-Saturation:	Readout holds at full scale in fields up to 100 times the maximum reading
Temperature Range:	-20° to +50° C, -4° to +122° F
Timer:	Can set sampling periods of 1 minute to 40 hours
Averaging Periods:	Display updates every 3 seconds, showing the average for the past 90-second time period at normal levels. The Averaging period decreases as the radiation level increases.
Power:	One 9-volt alkaline battery; battery life 2,000 hours typical, 700 hours minimum at normal background radiation levels at sea level. Battery life decreases as radiation level rises.
Size:	150 x 80 x 30 mm (5.9" x 3.2" x 1.2")
Weight:	225 grams (8 oz) including battery
Options:	Computer software and cable available
Certifications:	CE Certified: Emissions: EN 55011:2009 + A1:2010 (Class B emissions limits); EN 61326-1: 2006 (Class B) RF Emissions Immunity: EN 61326-1:2006 (Annex C) Portable Test and Measurement Equipment; EN 61000-4-2: 1995 (ESD); EN 61000-4-3: 1997 (EM) RoHS Compliant; Meets WEEE standards



Alert Switches Alpha Window



For more informaton contact:

www.ete.co.th