

NEW

TEMP RH BLE 4.0 10M radius

Bluetooth Datalogger
REC 68.8 RH%
START STOP
MAX MIN
AZ 88362 Temp.+RH

Hanger & 3 magnet to fix on wall

88362

Baro. RH TEMP BLE 4.0 10M radius

Bluetooth Datalogger
REC 988.8 hpa
START STOP
MAX MIN
AZ 88363 T+RH+BARO

88363

Step 1
Completely programmable by users through smart devices

Step 2
Leave it in any place. And starting recording in many ways

Step 3
Check real time data on APP anytime
Download data to APP without stopping recording

Step 4
Stopping recording in many ways

Step 5
Press key to review max. & min. data while phone is not available

Step 6
Using APP to generate PDF report and send data out

10M radius

Bluetooth 4.0 Barometric Pressure, Humidity & Temperature logger 88362/88363

- Programming logger & download data wirelessly through advanced BLE 4.0 technology
- Saving your cost by collecting recording data in seconds
- Free iOS & Android APP are provided for smart devices
- Generate and send out PDF report through APP. Report contains data summary, graph and detailed data
- Big LCD provides real time data every 5 seconds.
- Dual color LED are used as status and alarm indicators



Model	88262	88263
Temp. range	NTC thermistor, -30~70°C , -22~158°F	
Temp. resolution	0.1°C , 0.1°F	
Temp. Accuracy	+/-0.5°C	
Humidity range	Capacitor, 0.1~99.9%rH	
Humidity resolution	0.1%rH	
Humidity Accuracy	+/-3% (at 25°C, 10~90%), others +/-5%	
Barometric pressure	300~1100hPa , 8.9~32.5inHg	
Baro. resolution	0.1hPa, 0.1inHg	
Baro. Accuracy	+/-3hpa (0~60C), +/-5hpa(-20~0C), Accuracy is not specified in another temp. Range.	
Sampling points	24K: T & 24K:RH	16K:T , 16K:RH, 16K:Baro
Meter size	Meter:70(L)*50(W)*23(T) mm ; LCD:30(L)*18(W)	
Operating temp.	-30~70°C	
Operating RH%	Humidity < 90%	
Storage temp.	-40~85°C	
Storage RH%	Humidity < 90%	
Weight	~70g	
Battery	1PC 3.0V CR2, 3 months life time	
Sampling interval	10 seconds to 120 minutes	
Start delay	0~1440 minutes, 10 mins/step	
Alarm range	Programmable from -30 to 70°C	
Alarm delay	0~720minutes, 5 mins/step	
Alarm type	Single Event, Cumulative, Disable	
Operation keys	2 Keys (Start/Stop key & Max/Min key)	
LED indicator	REC, High / Low alarm	
Standard package	Logger, batteries, manual, paper box	

Ordering Code

VZ88362AZ, 88362 logger
VZ88363AZ, 88363 logger



Contact :

EASTERN ENERGY CO.,LTD. (HEAD OFFICE)

40/4 Vitoondumri Rd., Banbueng, Banbueng, Chonburi 20170
Tel: 0-3844-6117 Fax: 0-3844-6200
Email: info@ete.co.th

2017.07 V4