

**DT-5300B** 

# DIGITAL EARTH RESISTANCE TESTER

Electronic Digital Earth Resistance Tester is direct replacement of the conventional hand generator type tester. It is designed for measurement of the resistance of earthing used in the electrical equipment as well as for measurement of ground resistivity. It can be used for measurements of the other low regular and liquid resistances. It can also be used for measurement of voltage AC, voltage DC and earth voltage. This instrument finds wide application for testing earthing installation in power based industries, telecommunication networks and

electrical traction systems etc.



# **DT-5300B**

# DIGITAL EARTH RESISTANCE TESTER



### Contact :

EASTERN ENERGY CO.,LTD. (HEAD OFFICE) 40/4 Vitoondumri Rd., Banbueng, Banbueng, Chonburi 20170 Tel: 0-3844-6117 Fax: 0-3844-6200 Email: info@ete.co.th

www.ete.co.th / www.eastern-energy.com

# DT-5300B Digital Earth Resistance Tester

## **Environmental Specifications**

Earth resistance range	20Ω, 200Ω, 2000Ω		
Display	Large LCD with dual display		
Multimeter function Range	200kΩ, 750VAC, 1000VDC		
Sampling Rate	2.5 times per second		
Zero Adjustment	Automatic adjustment		
Over Range Indicator	Number 1 of highest digit is displayed.		
Low Battery Indication	The 👫 - is displayed when the battery Voltage drop below the operating voltage		
Power	Auto Power Off		
Operating Temperature	0°C to 40°C (32°F to 104°F) and Humidity below 80% RH		
Storage Temperature	-10°C to 60°C (14°F to 140°F) and Humidity below 70% RH		
Power source	6x1.5V Size "AA" battery or Equivalent (DC9V)		
Dimensions	200(L) x 92(W) x 50(H) mm		
Weight	Approx 700g include battery		

## **Electrical Specifications**

Accuracies are specified in the way:  $\pm(...\%$  of reading +...digits) at 23°C  $\pm$ 5°C, below 80% RH.

### Earth resistance

Range	Resolution	Accuracy
20Ω	0.01Ω	±(2%+10d)
200Ω	0.1Ω	±(2%+3d)
2000Ω	1Ω	±(2%+3d)

### Earth voltage

Range	Resolution	Accuracy
200V	0.1V	±(3%+3d)

#### OHMS

Range	Resolution	Accuracy	<b>Overload Protection</b>
200kΩ	0.1kΩ	±(1%+2d)	250Vrms

### **DC Voltage**

Range	Resolution	Accuracy	Input Impedance	<b>Overload Protection</b>
1000V	1V	±(0.8%+3d)	10MΩ	1000Vrms

### AC Voltage

Range	Resolution	Accuracy	Input Impedance	<b>Overload Protection</b>
750V	1V	±(1.2%+10d)	10ΜΩ	750Vrms

### Accessories

Batteries, Instruction Manual, Test Leads, Spikes, Cables, Hard Carrying Case, Test Certificate.



#### **Contact :**

**EASTERN ENERGY CO., LTD. (HEAD OFFICE)** 

40/4 Vitoondumri Rd., Banbueng, Banbueng, Chonburi 20170 Tel: 0-3844-6117 Fax: 0-3844-6200 Email: info@ete.co.th

### www.ete.co.th / www.eastern-energy.com